

RACK  
CONVEYORS

## LB - 2780 - T CV

### Features

Modules.	Wash, double rinse, double drying and steam condenser
Speeds.	1
Production (Plates/hour).	1200
Basket dimension (mm).	500 x 500
Water connection.	3/4".
Necessary pressure supply waters down.	2 - 4 bars / 200 - 500 Kpa.
Drainage.	Ø 50 mm.
Upper arms number.	1
Lower arms number inferior.	1
Upper suppliers number.	4
Lower suppliers number.	4
Washing tank.	1
Advance pump power.	0,11 Kw.
Wash pump power.	0,736
Heating element tank.	9 Kw.
Heating element boiler.	18 Kw.
Drying heating element.	2 x 4 Kw.
Steam condenser.	0,07 Kw.
Total power.	36 Kw.
Dimensions (mm).	2780 x 830 x 1715
Voltage.	230 - 400V / III / 50 - 60 Hz.




### High performance.

Fixed wash system allowing for an even distribution of water and disinfectant and cleaning products throughout the entire wash cycle. The jets cover all of the dishes, all of the time.



### Easy to clean.

Pressed tank without welding and rounded corner. Bayonet wash arms can be removed with just a quarter twist and taken apart to be cleaned. Cleaner and better protected wash system.



In addition, they include one filter for separating the water in the tank from the dirt, an one filter shaped like a tray, which can be easily removed and cleaned. Optional steam condenser.

